

# Steward Telephone Green

Compliant to BS5839-9:2021



The OmniCare system offers a choice of outstation units which can be wired on the same loop from the control panel.

The BVOCET emergency/steward telephone unit is one of the options available on this versatile system.

[Click for more, including links to 'How to' Videos & Guides and related products.](#)

## OmniCare

### BENEFITS & FEATURES:

- Provides two-way, full duplex, speech communication.
- Self-powered from ring circuit, no local power source is required. Automatic battery backup is provided by the control panel in the event of a mains power failure.
- Green finish.
- With additional beacon (BVOCETB).
- Push catch door (slot lock version available BVOCETL).
- Addressable unit.
- The enclosure contains a rugged red handset with hearing aid compatible earpiece and loudspeaker.
- Calls are initiated upon opening the door. When answered, the user can talk to the operator either by lifting the handset or hands-free. Closing the door ends the call.
- Conference call facility between multiple steward telephones is available via the operator at the control panel.
- All outstations are in a loop circuit from control panel(s).
- Surface mountable (or flush mount with optional bezel).

### PRODUCT CODES:

- BVOCET - green emergency telephone, push door.
- BVOCETL - green emergency telephone, lock door.
- BVOCETB - push door + beacon.
- BVOCETLB - lock door + beacon.
- BVOCETBEZ - green bezel to enable flush mounting.



**Maintenance Service Contracts Available:**

**Complimentary Maintenance Log Book Available:**

EVC System Maintenance Log Book

**EMERGENCY VOICE COMMUNICATION  
STEWARD TELEPHONE**

  
**BALDWIN BOXALL**  
LEADING THE WAY TO SAFETY

## Specifications:

	Steward Telephone
Product code (push door)	BVOCET
Product code (lock door)	BVOCETL
Product code (push door with beacon)	BVOCETB
Product code (lock door with beacon)	BVOCETLB
Power supply	12-40V DC self powered from ring circuit
Power consumption	30mA @ 35V typical
Weight	3.5 kg
Humidity range	95% non-condensing
Temperature range	-10°C to +40°C
Indicators	System healthy
Finish	RAL 6024
Dimensions mm W x H x D	130 x 350 x 100
Bezel dimensions mm W x H (radius)	170 x 390 x (20)
Bezel cutout mm W x H	138 x 358
Knockouts/cable entry points	20 mm & 25 mm
Mounting position	Steward telephones should be placed at a height of 1.3-1.4m.

### SYSTEM REQUIREMENTS:

- A repeater unit (BVOCRIF) must be used if the distance between remotes exceeds 200m.
- Disabled refuge, advance disabled refuge, fire telephone, emergency/steward telephone, combined DRS/fire telephone and emergency assistance alarm units can be placed on the same loop.
- Typically 20-30 remotes per loop.
- Repeater units (BVOCRIF) are used to connect the emergency assistance alarms (DTAKIT) to the system. Up to two (3-part) DTAKITs can be connected to a BVOCRIF. (Alternatively one DTAKIT with an additional pull cord can be installed. Useful for rooms with two points of call, e.g. a toilet cubicle or shower area.)
- No local power required for any outstation, including emergency assistance alarms.

Download Cabling Information



**BALDWIN BOXALL**  
LEADING THE WAY TO SAFETY

Baldwin Boxall Communications Ltd  
Wealden Industrial Estate, Farningham Road,  
Crowborough, East Sussex, TN6 2JR, United Kingdom  
T: +44 (0) 1892 664422  
E: [hello@baldwinboxall.co.uk](mailto:hello@baldwinboxall.co.uk)  
W: [www.baldwinboxall.co.uk](http://www.baldwinboxall.co.uk)